



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(51) International Patent Classification 6 : B60R 21/20, 21/22	A1	(11) International Publication Number: WO 98/56620 (43) International Publication Date: 17 December 1998 (17.12.98)
(21) International Application Number: PCT/US98/07774 (22) International Filing Date: 22 April 1998 (22.04.98) (30) Priority Data: 08/871,243 9 June 1997 (09.06.97) US (71) Applicant: TEXTRON AUTOMOTIVE COMPANY INC. [US/US]; 750 Stephenson Highway, Troy, MI 48043 (US). (72) Inventors: LABRIE, Craig, B.; 59 Upper Factory Road, Dover, NH 03820 (US). ROGERS, Jimmy, C.; 543 Route 9, Berwick, ME 03901 (US). GRAY, John, D.; 279 Bridge Street, Union, NH 03887 (US). BATCHELDER, Bruce, A.; 45 Wadleigh Falls Road, Lee, NH 03824 (US). GALLAGHER, Michael, J.; 325 Winnacunnet Road, Hampton, NH 03842 (US). RHODES, Richard, D., Jr.; 13 Lil Nor Avenue, Somersworth, NH 03878 (US). (74) Agent: EVANS, John, C.; Reising, Ethington, Learman & McCulloch PLLC, P.O. Box 4390, Troy, MI 48099-4390 (US).		(81) Designated States: AL, AU, BA, BB, BG, BR, CA, CN, CU, CZ, EE, GE, IL, IS, JP, KP, KR, LC, LK, LR, LT, LV, MG, MK, MN, MX, NO, NZ, PL, RO, SG, SI, SK, TR, TT, UA, UZ, VN, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report.

(54) Title: APPARATUS FOR DEPLOYING AN AIR BAG THROUGH A HARD PANEL

(57) Abstract

An apparatus (10) for deploying an air bag (24) through an automotive dash panel (12) includes an air bag door (16) integrally formed in the panel (12) and defined by a frangible edge (18) of reduced cross section. A dispenser (20) supports the air bag (24) behind the door (16). A metal reaction plate (28) is positioned between the air bag (24) and the door (16). When the air bag (24) inflates it forces the reaction plate (28) to bend around a horizontal hinge line (36). As the reaction plate (28) rotates it concentrates inflation force along a lower portion (120) of the frangible door edge (18). This helps predictably separate the door (16) from the dash panel (12) by tearing along the lower door edge (120) and allowing the tear to propagate up two side edges (122). In one embodiment, the tear also propagates across an upper edge (124) to completely separate the door from the panel (12). At least one, and preferably

two or three tethers (50) limit how far the door can travel during air bag inflation. A stop member (96) may be included to limit reaction plate (28) bending. After deployment, the reaction plate (28) remains in a position that prevents the door (16) from returning to its original position.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

APPARATUS FOR DEPLOYING AN AIRBAG THROUGH A HARD PANEL

TECHNICAL FIELD

5

This invention relates generally to a passive supplemental inflatable restraint (PSIR) system having a PSIR door that is integrally formed with an instrument panel and, more particularly, to such a system having a PSIR door integrally formed with a hard first-surface instrument panel.

10

BACKGROUND OF THE INVENTION

A passive supplemental inflatable restraint system having a PSIR door that is integrally formed into an automotive vehicle instrument panel must also include some provision for guiding or otherwise facilitating the opening and partial separation of that PSIR door from the instrument panel that it is integrally formed with. This is particularly true of PSIR doors that are integrally formed into hard first-surface instrument panels. The "first-surface" of a panel is the cosmetic exterior surface that would be visible to a vehicle occupant. Hard first-surface panels are typically formed by injection molding one or more plastic materials.

20

To close air bag deployment openings in hard first-surface instrument panels, many current PSIR systems use a separate "add-on" PSIR door. One reason that current PSIR systems add on a separate PSIR door in such applications is because it is difficult to cause a tear seam to break and/or tear in a predictable way under the sudden shock of a deploying air bag. Even when weakened, a tear seam that integrally joins a PSIR door and a surrounding instrument panel can fracture in a ragged unpredictable manner that can affect air bag deployment.

25

One example of a hard first-surface system is disclosed in United States Patent Number 5,472,228 assigned to Morton International and issued December 5, 1995. This patent discloses a reinforced hard door with a

30

reaction plate. When the air bag deploys, the reaction plate forces the door in a direction that will break weakened fasteners securing the door to an instrument panel.

Another of Morton's hard door concepts is shown in United States
5 Patent Number 5,533,746, issued July 9, 1996. This system includes a reaction plate with reinforced lands. When the air bag deploys, it acts upon the reaction plate to cause hold down attachment rods to release from clips.

What is needed is an apparatus that, in response to air bag deployment, helps separate and open a PSIR door that is integrally formed
10 into an instrument panel. What is also needed is such an apparatus that helps separate and open a PSIR door that is integrally formed into a hard first-surface instrument panel.

SUMMARY OF THE INVENTION

15 A passive supplemental restraint apparatus 10, 10', 10'', 10s for an automotive vehicle comprises an interior vehicle panel 12, 12', 12'', 12s and an air bag deployment door 16, 16', 16'', 16s integrally formed in the vehicle panel 12, 12', 12'', 12s. The air bag deployment door 16, 16', 16'', 16s has a
20 perimeter, at least a portion of which is defined by a frangible marginal edge 18, 18', 18'', 18s. An air bag dispenser 20, 20', 20'', 20s is supported adjacent a door inner surface 38, 38', 38'', 38s opposite a door outer surface 22, 22', 22'', 22s. An air bag 24, 24', 24'', 24s is supported in an air bag receptacle 26, 26', 26'', 26s of the air bag dispenser 20, 20', 20'', 20s. The air
25 bag 24, 24', 24'', 24s has an inner end 27, 27', 27'', 27s operatively connected to the air bag dispenser 20, 20', 20'', 20s and an outer end 30, 30', 30'', 30s disposed adjacent the air bag deployment door 16, 16', 16'', 16s. Characterizing the invention is a reaction plate 28, 28', 28'', 28s disposed between the air bag 24, 24', 24'', 24s and the air bag deployment door 16, 16',
30 16'', 16s.

The present invention is different from prior art passive supplemental restraint systems in that it includes a reaction plate positioned to receive the force of air bag deployment from the dispenser 20, 20', 20'', 20s. The reaction plate then directs and distributes that force against the door inner surface 38, 38', 38'', 38s. In this way the reaction plate concentrates air bag opening forces along the frangible marginal edge 18, 18', 18'', 18s of the door 16, 16', 16'', 16s causing the door 16, 16', 16'', 16s to separate from the vehicle panel 12, 12', 12'', 12s along the frangible marginal edge 18, 18', 18'', 18s.

BRIEF DESCRIPTION OF THE DRAWINGS

To better understand and appreciate the invention, refer to the following detailed description in connection with the accompanying drawings:

Figure 1 is a perspective view of a first passive restraint system constructed according to the present invention and installed in a vehicle dash panel;

Figure 2 is a cross-sectional end view of the passive restraint system of Fig. 1;

Figure 3 is an exploded view of the passive restraint system of Fig. 1;

Figure 4 is a cross-sectional end view of a second passive restraint system constructed according to the present invention;

Figure 5 is a fragmentary perspective view of a PSIR door of the passive restraint system of Fig. 4;

Figure 6 is a fragmentary perspective view of the PSIR door of Fig. 5 installed in a vehicle dash panel;

Figure 7 is a cross-sectional end view of the passive restraint system of Fig. 4 during air bag inflation;

Figure 8 is a cross sectional view of a heat-stake pin of the passive restraint system of Figs. 1 and 2;

Figure 9 is a perspective view of a third passive restraint system constructed according to the present invention and installed in a vehicle dash panel;

Figure 10 is a cross-sectional view of the passive restraint system of Fig. 9 taken along line 10-10 of Fig. 9;

Figure 11 is a cross-sectional view of the passive restraint system of Fig. 9 taken along line 10-10 of Fig. 9 during air bag inflation;

Figure 12 is a first cross-sectional view of a fourth passive restraint system constructed according to the present invention;

Figure 13 is a cross-sectional view of the passive restraint system of Fig. 12 during air bag inflation;

Figure 14 is a cross-sectional view of the passive restraint system of Fig. 12 taken through a screw boss of the system;

Figure 15 is a cross-sectional view of the passive restraint system of Fig. 12 taken through a screw boss of the system during air bag inflation;

Figure 16 is a cross-sectional view of the passive restraint system of Fig. 12 taken along line 16-16 of Fig. 14; and

Figure 17 is a partial cross-sectional view of the passive restraint system of Fig. 10 including an alternative tether attachment construction.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A first embodiment of a passive supplemental restraint apparatus for an automotive vehicle is generally indicated at 10 in Figs. 1-3. A second embodiment is generally indicated at 10' in Figs. 4-7. A third embodiment is generally indicated at 10'' in Figs. 9-11. Reference numerals with the designation prime (') in Figs. 4-7 and double prime (") in Figs. 9-11 indicate alternative configurations of elements that also appear in the first embodiment. Where a portion of the following description uses a reference numeral to refer to the figures, we intend that portion of the description to

apply equally to elements designated by primed numerals in Figs. 4-7 and double-primed numerals in Figs. 9-11.

In Fig. 1 the passive supplemental restraint apparatus is shown hidden behind an automotive vehicle passenger-side dash panel 12 below a windshield 14 of the vehicle. As shown in Fig. 2, the apparatus includes the panel 12, and an air bag deployment door 16 integrally formed in the panel 12 and having a perimeter defined, in part, by a hidden marginal edge 18. The perimeter may, also be defined as the lateral boundary of the door 16 - the door 16 being defined as that portion of the integrally formed panel 12 and door 16 that is separable or bendable from the panel 12 under the force of air bag inflation. The door 16 and the vehicle dash panel 12 are integrally formed as a single unitary piece.

As shown in Figs. 2 and 3, an air bag dispenser assembly 20 is supported behind the door 16, i.e., on a side of the door 16 opposite a door outer surface 22. The dispenser 20 is also disposed adjacent and aligned with the air bag deployment door 16. The dispenser 20 may be any suitable type of air bag dispenser to include, for example, the dispenser described in U.S. patent number 5,564,731 and incorporated herein by reference.

An air bag 24 is supported in an air bag receptacle 26 of the air bag dispenser 20 and is operatively connected to the air bag dispenser 20 at an open end 27 of the air bag 24. A closed outer end 30 of the air bag 24 is disposed adjacent the air bag 24 deployment door 16.

As is best shown in Fig. 2, a rigid metal reaction plate 28 is disposed between the air bag 24 and the air bag deployment door 16. The reaction plate 28 receives the force of air bag deployment when the air bag 24 inflates and expands out of the dispenser 20. The reaction plate 28 directs and distributes that force across the door 16 to predictably separate the door 16 from the panel 12 along the hidden marginal edge 18 of the door 16. By distributing the air bag 24 opening force across the door 16 the reaction plate 28 also serves to prevent air bag 24 opening forces from concentrating in other locations on the door 16 that might result in door 16 or panel 12 fractures and/or fragmentation. In the present embodiment, the reaction plate

28 is positioned to concentrate air bag opening forces along a portion of the hidden marginal edge 18 that extends along the forward marginal edge 46 of the door 16. The reaction plate 28 is positioned in this way to initiate marginal edge tearing at the forward marginal edge 46 and then allow the tearing to propagate upward along the two side edges of the door 16. Alternatively, marginal edge tearing may be initiated at the forward marginal edge 46 and along the two side edges virtually simultaneously. The reaction plate 18 is preferably made of cold rolled steel but may be made from any other material having suitable bending and force-distributing characteristics.

As is best shown in Fig. 3, the reaction plate 28 includes a reaction plate outer marginal edge 32 having a shape generally identical to that of the hidden marginal edge 18 of the air bag deployment door 16. The reaction plate marginal edge 32 is aligned with the hidden marginal edge 18 of the air bag deployment door 16 to concentrate air bag 24 inflation stress along the hidden marginal edge 18 of the air bag deployment door 16.

As shown in Fig. 2, the reaction plate 28 is pivotally attached along a reaction plate inner edge 34 to the air bag dispenser apparatus 20. However, in other embodiments, the reaction plate 28 may be pivotally attached to a portion of the panel 12 or other surrounding support structures. An outer portion of the reaction plate 28, generally indicated at 35 in Figs. 2 and 3, is outwardly and upwardly pivotable away from the air bag dispenser 20. The outer reaction plate portion 35 pivots by bending along a first horizontal hinge line 36 of the reaction plate 28 that extends parallel to and adjacent the rigidly attached inner plate edge 34. The hinge line 36 defines a marginal inner edge of the outer portion 35 of the reaction plate. The outer portion 35 of the reaction plate also pivots by bending along a second horizontal hinge line 37 of the reaction plate 28 that extends parallel to the first hinge line 36.

As shown in Fig. 2, the outer portion 35 of the reaction plate 28 is disposed adjacent a door inner surface 38 and opposite the outer door surface 22. Three horizontal ribs, shown at 40 in Figs. 2 and 3, extend integrally inward from the door inner surface 38 to a point adjacent a lower panel 42 of the outer portion 35 of the reaction plate as shown in Figs. 2 and 3. The ribs

40 space the reaction plate lower panel 42 from the door inner surface 38. The ribs 40 allow the reaction plate 28 to be positioned in a plane that is generally perpendicular to the direction of air bag 24 deployment while remaining in close proximity to the door 16. The ribs 40 also allow the door 16 to be
5 designed with outer contours that do not necessarily correspond to the reaction plate 28 configuration. In other embodiments the ribs 40 may be of any suitable configuration and orientation known in the art.

As shown in Figs. 1-3, the air bag deployment door 16 has a curved rectangular shape defined by relatively straight aft 44 and forward 46
10 marginal edges and a pair of arcuate side marginal edges 48. The forward 46 and side 48 edges comprise a frangible region of reduced cross section. The rear edge 44 may comprise a styling seam or groove intended to define the rear edge 44 of the door 16. In other embodiments the rear edge 44 may be hidden or there may be no "rear edge". In other words, the transition from
15 the door to the panel 12 may be uninterrupted.

Where a styling seam is used it may be functional or merely aesthetic. Where the styling seam is functional, it may be adapted to act as a bending hinge 44 when the door 16 is forced open and separated from the surrounding vehicle panel 12 along the frangible forward 46 and side 48
20 marginal edges. The bending hinge 44 allows the door 16 to swing outward and upward from the panel 12 during air bag 24 deployment while retaining the door 16 to the panel 12. Alternatively, the styling seam may also be designed as a frangible region of reduced cross section in similar fashion to the forward 46 and side 48 edges.

25 A first pair of flexible tethers are generally indicated at 50 in Figs. 2 and 3. Each tether comprises PVC-coated nylon and has an outer end portion 52 fastened to the door inner surface 38 and an inner end portion 54 fastened to the air bag dispenser assembly 20. In other embodiments the first pair of flexible tethers 50 may be fastened to the panel 12 or other adjacent
30 support structures instead of the dispenser 20. The tethers 50 may incorporate any one or more of a number of different tether constructions known in the art. One example of an acceptable tether construction is disclosed in United

States patent number 5,564,731, is assigned to the assignee of the present invention and is incorporated herein by reference.

The inner end portion 54 of each tether 50 of the first pair of tethers is fastened to the air bag dispenser assembly 20 at a tether control point shown at 56 in Fig. 2 adjacent the reaction plate inner edge 34. The tether inner end portions 54 are fastened by folding them within a U-shaped channel 58 formed along the reaction plate inner edge 34. As shown in Fig. 3, a row of holes 60 is formed along each side of the U-shaped reaction plate channel 58 to receive fasteners 62 that attach the reaction plate 28 to an elongated rectangular air bag dispenser flange 64. The dispenser flange 64 is horizontally disposed and extends integrally upward from the air bag dispenser apparatus 20. The flange 64 includes a row of flange holes 66 corresponding to the holes in the U-shaped reaction plate channel 58. One or more of the fasteners that connect the reaction plate 28 to the dispenser assembly 20, also pass through the portion of each tether inner end 54 that is folded within the U-shaped channel 58.

As is best shown in Fig. 2, the outer end portion 52 of each tether 50 of the first pair of tethers is fastened to the door 16 by eight heat-staked pins 68. The pins 68 extend integrally inward from the air bag 24 deployment door 16 as shown in Fig. 8. The pins 68 are preferably formed with the door 16 and the vehicle panel 12 as a single unitary piece. Other embodiments may use hot staked bosses as disclosed in United States patent number 5,564,731, assigned to the assignee of the present invention and incorporated herein by reference. Still other embodiments may use screws 76b engaged with screw bosses as is representatively shown at 67 in Fig. 17. The screw bosses 67 may be integrally formed to extend inward from the door 16. The bosses 67 may be threaded or unthreaded for use with self-tapping screws. Other embodiments may use any number of suitable fastening means known in the art.

The air bag dispenser apparatus 10 described above is optimized to open integral doors in instrument panels, comprising hard outer or "first" surfaces, e.g., injection-molded panels. However, the invention may also be

used where, as shown in Fig. 2, the hard outer surface is covered with a flexible skin 69 or skin 69 and foam 71 layers. In other words, a flexible skin 69 may be applied to cover at least a portion of the vehicle dash panel 12 and/or air bag deployment door 16 in a layered disposition. A foam layer 5 71 may also be included between the skin 69 and a portion of the panel 12 and/or the door 16.

The door 16 and panel 12 preferably comprise an injection molded polycarbonate/acrylonitrile butadiene styrene blend (PC/ABS) or polypropylene. Examples of acceptable PC ABS formulations include GE 10 MC 8002 and Dow Pulse # 830. An example of an acceptable polypropylene is Montell #BR33GC. Other suitable materials may include polyesters, polyurethanes, polyphenylene oxide, polystyrenes, polyolefins, or polyolefin elastomers.

According to the second embodiment of the invention shown in 15 Figs. 4-7, the air bag deployment door 16' is defined by a visible marginal edge 18' and includes eight doghouse-shaped fastener brackets 70. Each fastener bracket 70 extends integrally inward toward the air bag dispenser assembly 20' from the door inner surface 38' in place of the ribs 40 of the first embodiment. Each fastener bracket 70 includes an attachment surface 72 20 spaced inwardly from and supported generally parallel to the door inner surface 38'. The fastener brackets 70 are preferably integrally formed with the door 16' and the vehicle dash panel 12' as a single unitary piece.

The first tether 50' of the second embodiment makes up a portion of a single continuous tether sheet rather than comprising two separate tethers 25 as in the first embodiment. As shown in Figs. 4-7, an outer end 52' of the first tether 50' is attached to a forward portion 74 of the door 16' adjacent a forward marginal edge 46' of the door 16' disposed opposite the hinge 44'. More specifically, four rivets 76 attach the outer end 52' of the first tether 50' to the attachment surfaces 72 of four fastener brackets 70 formed on the 30 forward portion 74 of the door 16. The fastener brackets 70 support the rivets 76 without affecting the aesthetic continuity of the outer door surface 22'. In other embodiments, other fastener bracket configurations including heat

staking pins and screw bosses and other suitable types of fasteners and fastening methods may be used as is known in the art.

As shown in Figs. 4 and 7, each fastener bracket 70 includes a fastener aperture 78 disposed through the attachment surface 72 of the bracket 70 to receive one of the rivets 76. Each rivet 76 comprises a shaft portion that extends through the aperture 78 and also through a hole formed in the first tether 50' to hold the first tether 50' to the fastener bracket 70 in conventional fashion.

The four fastener brackets 70 that attach the first tether 50' to the door 16' extend integrally inward from the door inner surface 38' adjacent a lower marginal region of the door 16' to a point adjacent the reaction plate 28'. Similar to the ribs 40 of the first embodiment, the fastener brackets 70 present the reaction plate lower panel 42' in a plane more perpendicular to the direction of air bag 24' deployment from the dispenser 20'. In other words, the fastener brackets 70 span the space between the outwardly curved lower marginal door region and the generally vertical reaction plate lower panel 42'.

The single continuous tether sheet that includes the first flexible tether 50' also includes a second flexible tether, generally indicated at 80 in Figs. 4 and 7. The second tether 80 has an inner end portion 82 fastened to the air bag dispenser assembly 20' at the tether control point 56'. In other embodiments the second tether 80 may be secured either to the panel 12' or to another adjacent structure. The second flexible tether 80 has an outer end portion, shown at 84 in Figs. 4 and 7, that is fastened to an aft portion 86 of the door 16' disposed between the forward door portion 74 and the hinge 44'. The second tether 80 ties the aft door portion 86 to the control point 56' to prevent any portion of the door from over-rotating towards the windshield 14 and breaking off at one of several potential bending points including the hinge 44.

As shown in Figs. 4 and 7, the respective inner ends 54', 82 of the first 50' and second 80 tethers are riveted to an elongated rectangular flange 64' at the tether control point 56'. The flange 64' extends integrally upward from the air bag receptacle portion 26' of the air bag dispenser assembly 20'.

The tether inner ends 54', 82 are sandwiched between the flange 64' and an elongated metal bar 90. Rivets 92 pass through the flange 64', the tethers 50', 80 and the bar 90.

5 The air bag receptacle 26' includes a mouth 94 disposed adjacent the air bag deployment door 16'. The mouth 94 has a width measured across the mouth in a direction perpendicular to the hinge 44', i.e., in a generally vertical direction. The hinge 44' is spaced from the mouth 94 a distance equal to at least half of the mouth width. The hinge 44' is displaced in this manner to reduce the maximum opening angle at the hinge 44' to reduce material
10 deformation and stress in the hinge during air bag 24 deployment.

A pair of rigid stop members, representatively indicated at 96 in Fig. 7, are operatively connected to the reaction plate 28' and the air bag dispenser 20'. The stop members 96 limit reaction plate 28' opening travel. The stop members 96 may arrest the reaction plate 28 in a position that will
15 prevent the door 16' from returning to its original position after air bag 24 deployment. Each stop member is preferably fabricated from steel but may be made of other suitably rigid materials.

The stop members 96 are slidably supported in slots representatively shown at 98 in Fig. 7 and disposed at opposite lateral sides of the receptacle portion 26' of the air bag dispenser apparatus 20'. Each stop
20 member 96 is fixed to the reaction plate 28' at a stop point representatively shown at 100 in Fig. 7. The stop point 100 disposed between the first hinge line 36' and a reaction plate outer marginal edge 32' disposed opposite the reaction plate inner edge 34'.

25 The outer panel portion 42' of the reaction plate 28' is outwardly and upwardly pivotable away from the air bag dispenser 20' by bending the reaction plate 28' along a second horizontal hinge line shown at 102 in Fig. 7. The second hinge line 102 is disposed horizontally across the reaction plate 28' adjacent the stop point 100 and extends generally parallel to the first hinge
30 line 36'. The second hinge line 102 is spaced approximately one-third the distance between the first hinge line 36' and the reaction plate outer marginal edge 32'. This double hinge arrangement allows the reaction plate 28' to bend

into an outwardly-rotated and upwardly extended position. In this position the plate 28' prevents the air bag deployment door 16' from rebounding off the tethers 50', 80 and returning to its original position immediately after a deploying air bag 24' has forced the door 16' open.

5 Each stop member 96 is an elongated steel pin having a cylindrical shaft portion 104 as is representatively shown in Fig. 7. Inner 106 and outer 108 circular disk-shaped stop flanges are disposed at respective inner and outer distal ends of the shaft portion 104 of each stop member 96. The inner stop flange 106 of each stop member 96 extends radially and integrally
10 outward from the shaft portion 104. The outer stop flange 108 of each stop member 96 is preferably fixed to the reaction plate 28' by spot welding or arc welding.

 The elongated slots 98 on either side of the air bag receptacle 26 each have a width slightly greater than that of the shaft portion 104 of each
15 stop member 96. The shaft portion 104 of each stop member 96 is slidably disposed within one of the slots 98 to allow the stop members 96 to move between pre-inflation stowed positions, representatively shown in Fig. 4, and post-inflation deployed positions, representatively shown in Fig. 7. The reaction plate 28' pulls the stop members 96 from the stowed position to
20 the deployed position when the reaction plate 28' opens under the force of an inflating air bag 24'. When the stop members 96 reach their deployed positions the inner stop flanges 106 engage the slot 98 and arrest reaction plate 28' movement. The stop members 96 arrest the reaction plate 28' in a position to prevent the door 16' from returning to its original position
25 following air bag deployment.

 According to the third embodiment of the invention shown in Figs. 9-11, the frangible marginal edge 18" defines the entire perimeter of the air bag deployment door 16". In other words, the frangible marginal edge 18" extends completely around the air bag deployment door 16" in an unbroken
30 circuit as is best shown in Fig. 9. A pair of flexible tethers, representatively indicated at 50" in Figs. 10 and 11, is fastened between the air bag deployment door 16" and the reaction plate 28". Each tether 50" includes an

inner end portion 82" fastened to the door 16", an outer end portion 84" fastened to the door 16" and a middle portion 83 fastened to the reaction plate 28" between the second hinge line 102" and the reaction plate outer marginal edge 32". The middle portion 83 of each tether 50" is disposed approximately
5 midway between the inner 82" and outer 84" end portions of each tether 50".

The air bag deployment door 16" includes only four of the fastener brackets 70" disposed in a rectangular pattern as shown in Fig. 9. The inner end portion 82" and outer end portion 84" of each tether 50" are fastened to the attachment surface of one of the four fastener brackets 70" by rivets 76"
10 as shown in Figs. 10 and 11. As is also shown in Figs. 10 and 11, the middle portion 83 of each tether 50" is fastened to the reaction plate 28" between the second hinge line 102" and the reaction plate outer marginal edge 32" by a rivet 110.

As shown in Figs. 9-11, nine vertical door ribs 112 extend
15 integrally inward from the door inner surface 38" to a point adjacent the reaction plate 28". 24 short horizontal door ribs 114 connect adjacent vertical door ribs 112 to form a rectangular grid pattern best shown in Fig. 9. As best shown in Fig. 9, a plurality of vertical 116 and horizontal 118 panel ribs also extend integrally inward from an inner surface of the vehicle panel 12"
20 adjacent the frangible marginal edge 18" of the door perimeter and are spaced apart around the door perimeter. The door ribs 112, 114 and panel ribs 116, 118 stiffen the door 16" and vehicle panel 12" against air bag opening shock and help concentrate opening forces along the frangible marginal edge 18" between the panel 12" and the door 16". The door ribs 112, 114 and panel ribs
25 116, 118 are integrally formed with the door 16" and the vehicle panel 12" as a single unitary piece by injection molding.

In practice, when the air bag inflates it forces the reaction plate 28" to bend outward and upward around the first 36" and second 102" horizontal hinge lines. As the reaction plate 28" rotates outward it
30 concentrates the inflation force along a lower edge portion 120 of the frangible door edge 18". This helps to predictably separate the door 16" from the vehicle dash panel 12" by tearing first along a lower edge portion

120 of the marginal edge 18" of the door 16" then allowing the tear to propagate up two side edge portions 122 of the door edge 18". The tear then propagates from the side edge portions 122 inwardly along an upper edge portion 124 of the marginal door edge 18" until the door 16" completely separates from the vehicle dash panel 12". Because the two tethers 50" connect the door 16" directly to the reaction plate 28", they prevent the door 16" from flying free. Similar to the second embodiment, the stop members 96" of the third embodiment limit how far the reaction plate 28" can bend, leaving the reaction plate 28" in an a generally vertical position. Unlike the second embodiment, however, the upwardly-bent reaction plate 28" and the tethers 50" of the third embodiment hold the air bag deployment door 16" away from vehicle occupants. Alternatively, tearing may occur along the lower edge portion 120, side edge portions 122 and upper edge portion 124 virtually simultaneously.

15 In other embodiments, in place of the pin and slot arrangement described for the stop member above, any one of a number of different configurations may be employed to arrest reaction plate 28 travel in a position to prevent an air bag door 16 from returning to its original position.

A fourth embodiment of a passive supplemental restraint apparatus is generally shown at 10s in Figs. 12-16. Reference numerals with the suffix "s" in Figs. 12-16 indicate alternative configurations of elements that also appear in the third embodiment. Where portions of the third embodiment description use reference numerals to refer to the figures, we intend those portions to apply equally to elements designated by the suffix "s" in Figs. 12-16.

The passive supplemental restraint apparatus generally indicated at 10s includes first and second vertically-disposed elongated flexible nylon tethers, generally indicated at 50s, 51s in Fig. 16, and representatively indicated at 50s in Figs. 12 and 13. The tethers 50s, 51s slidably engage the door 16s rather than being fixed to the door 16s as disclosed in the description of the third embodiment. The apparatus 10s includes a flat, elongated flexible nylon fabric strap, generally indicated at 126 in Figs. 12-

16. The strap 126 has a length extending between two strap ends and is horizontally disposed flat against the door 16s. As is best shown in Fig. 16, the strap 126 is fastened to the door 16s at first, second, third and fourth spaced attachment points 128, 130, 132, 134.

5 Each flexible tether 50s, 51s includes a tether loop, representatively shown at 157 in Figs. 12 and 13. The loop portion 157 of each tether 50s, 51s extends from at least one common tether loop attachment portion. In the present embodiment, the tether loop attachment portions each comprise first and second tether loop ends, representatively shown at 156, 158 in Figs. 12
10 and 13. Fasteners 161 extend through a strap retention member 163, both tether loop ends 156, 158, the reaction plate 28s and the air bag dispenser 20s. The fasteners 161 fasten the tether loop ends 156, 158 together, and fasten the loop ends 156 and reaction plate 28s to the air bag dispenser 20s adjacent the reaction plate inner edge 34. In other embodiments the first tether loop end
15 156 of each tether 50s, 51s may be attached at a different location than the second tether loop end 158 of each tether 50s, 51s.

 A middle portion 136 of the first flexible tether 50s slidably extends between the door 16s and the strap 126, perpendicular to the length of the strap 126, and passes between the first and second attachment points
20 128, 130. Likewise, a middle portion 138 of the second flexible tether 51s slidably extends between the door 16s and the strap 126, perpendicular to the length of the strap 126, and passes between the third and fourth attachment points 132, 134. In other words, the strap 126 holds the flexible tethers 50s, 51s against the door 16s while allowing the flexible tethers 50s,
25 51s to slide longitudinally through a pair of slots 140, 142. The slots 140, 142 are formed between the strap 126, the door 16s and the attachment points 128-134 as best shown in Figs. 12, 13 and 16.

 The apparatus (10s) includes first, second, third and fourth screw bosses, shown at 144, 146, 148 and 150 in Fig. 16 and representatively
30 shown at 144 in Figs. 14 and 15. The bosses 144-150 extend integrally inward from a door inner surface 38s to the respective first, second, third and fourth attachment points 128-134. The screw bosses 144-150 are

integrally formed with the door 16s as a unitary piece and are aligned horizontally along the door inner surface 38s. As shown in Figs. 14-16, screw-type fasteners 152 extend through respective annular washers 154 and attach the strap 126 to the respective first, second, third and fourth
5 bosses 144-150 by threadedly engaging the bosses 144-150.

As with the first and second embodiment, a generally rectangular reaction plate 28s is attached to an air bag dispenser assembly 20s along a reaction plate inner edge 34s, as shown in Figs. 12-15. An outer portion 35s of the reaction plate 28s is outwardly pivotable away from the air bag
10 dispenser assembly 20s by bending the reaction plate 28s along a hinge line 36s extending parallel to the reaction plate inner edge 34s. Prior to air bag inflation, the reaction plate 28s is bent at the hinge line 36s approximately 85° downward from horizontal. Following air bag inflation, the reaction plate 28s is bent approximately 85° upward from horizontal.

Each flexible tether 50s, 51s has a length extending between first and second tether ends, representatively shown at 156 and 158, respectively, in Figs. 12 and 13. The first and second tether ends 156, 158 of each flexible
15 tether 50s, 51s are fastened to the air bag dispenser assembly 20s adjacent the reaction plate inner edge 34s forming tether loops as shown in Figs. 12 and 13.

A middle tether portion 160 of the first flexible tether 50s, 51s slidably engages the outer portion 35s of the reaction plate 28s. Likewise, a middle tether portion of the second flexible tether 51s slidably engages the outer portion 35s of the reaction plate 28s at a point spaced laterally from the
20 point where the first flexible tether 50s engages the outer portion 35s of the reaction plate 28s. As shown in Figs. 12, 13 and 16, respective outer portions 162, 164 of the flexible tethers 50s, 51s, disposed between the middle tether portions 160 and the first tether ends 156 slidably extend between the
25 door 16s and the strap 126 as described above.

As shown in Figs. 12 and 13, the first flexible tether 50s slidably
30 extends through a first opening or slot in the outer portion 35s of the reaction plate 28s adjacent a reaction plate outer marginal edge 32s. Likewise, the second flexible tether 51s slidably extends through a second

slot, spaced laterally from the first slot along the reaction plate outer marginal edge 32s.

According to the fourth embodiment, when the air bag inflates, it forces the reaction plate 28s to bend outward and upward around the horizontal hinge line 36s. As the reaction plate 28s rotates outward it concentrates the inflation force along a lower edge portion 120s of the frangible door edge 18s. This begins tearing that advances around the entire door edge 18s and separates the door 16s from the vehicle dash panel 12s. Similar to the third embodiment, the first and second tethers 50s, 51s of the fourth embodiment connect the door 16s to the reaction plate 28s to decelerate and prevent the door 16s from flying free.

Unlike the third embodiment, however, the tethers 50s, 51s of the fourth embodiment allow the door 16s to slide along a portion of their lengths. The sliding prevents the loads exerted by door 16s on the tethers 50s, 51s from concentrating at any one attachment point along the tethers 50s, 51s. The sliding also spreads the door arresting shock over time, reducing the probability of the door 16s fracturing or pulling loose from the tethers 50s, 51s.

Although air bag inflation eventually causes the door to tear free along an upper edge portion 44s of the door perimeter 18s, the upper edge portion 44s initially acts as a living hinge. The door 16s initially swings outward and upward about the upper edge portion 44s while remaining in direct contact with the reaction plate 28s.

During this initial opening swing, the plate 28s and the door 16s rotate around different axes because the upper edge portion 44s is offset from the reaction plate hinge line 36s. Because the upper edge 44s and hinge line 36s are offset, and because the tethers 50s, 51s are slidably engaged with the plate 28s and the door 16s, the tethers 50s, 51s are able to hold the plate 28s and door 16s in close proximity to one another without arresting or overly restricting their movement.

The tethers 50s, 51s offer little resistance from the time the door 16s is initially forced open until the door 16s and reaction plate 28s reach

an approximately horizontal position. However, when the reaction plate 28s reaches this horizontal position, the door 16s tears loose from the upper edge 44s and is arrested by the tethers 50s, 51s. As the reaction plate 28s moves through the horizontal and continues to swing upward toward its fully open near-vertical position, the reaction plate 28s rapidly decelerates. As the reaction plate 28s decelerates, the tethers 50s, 51s allow the door 16s to swing upwards, absorbing energy as the tethers 50s, 51s slide through the slots 168, 170 in the reaction plate and through the gap between the horizontal strap 126 and the door 16s.

Preferably the tethers 50s, 51s and horizontal strap 126 are both made of nylon fabric. However, any one of a number of other suitable materials may be used to construct the tethers 50s, 51s and/or the strap 126, to include thin metal straps. In addition, a slotted insert may be used, in place of a strap, to slidably retain the tethers 50s, 51s. In other words, the tethers 50s, 51s; strap 126; reaction plate 28s; door 16s; and offset pivot points 36s, 44s make up a compound-swing tether system that eliminates lash and absorbs door opening forces.

Other possible variations on the fourth embodiment include the strap 126 being made of some flexible material other than fabric. Moreover, the strap 126 need not be flat, but may be of any cross-sectional shape, e.g., a cord-like structure having a circular cross-section. The reaction plate 28s and/or tether ends 156, 158 could be attached to the vehicle panel 12s rather than the air bag dispenser 20s along the reaction plate inner edge 34s. In addition, in other embodiments the tethers 50s, 51s need not slidably engage the reaction plate 28s. Instead, the tethers 50s, 51s may be fixed to the reaction plate 28s at some point along their respective lengths.

The description and drawings illustratively set forth our presently preferred invention embodiments. We intend the description and drawings to describe these embodiments and not to limit the scope of the invention. Obviously, it is possible to modify these embodiments while remaining within the scope of the following claims. Therefore, within the

scope of the claims, one may practice the invention otherwise than as the description and drawings specifically show and describe.

I claim:

1. A passive supplemental restraint apparatus (10, 10', 10'', 10s) for an automotive vehicle, the apparatus comprising:

5 an interior vehicle panel (12, 12', 12'', 12s);

an air bag deployment door (16, 16', 16'', 16s) integrally formed in the vehicle panel (12, 12', 12'', 12s), the air bag deployment door (16, 16', 16'', 16s) having a perimeter, at least a portion of the perimeter defined by a frangible marginal edge (18, 18', 18'', 18s);

10 an air bag dispenser (20, 20', 20'', 20s) supported adjacent a door inner surface (38, 38', 38'', 38s) opposite a door outer surface (22, 22', 22'', 22s);

an air bag (24, 24', 24'', 24s) supported in an air bag receptacle (26, 26', 26'', 26s) of the air bag dispenser (20, 20', 20'', 20s), the air bag (24, 24', 24'', 24s) having an inner end (27, 27', 27'', 27s) operatively connected to the air bag dispenser (20, 20', 20'', 20s) and an outer end (30, 30', 30'', 30s) disposed adjacent the air bag deployment door (16, 16', 16'', 16s); the apparatus (10, 10', 10'', 10s) characterized by:

20 a reaction plate (28, 28', 28'', 28s) disposed between the air bag (24, 24', 24'', 24s) and the air bag deployment door (16, 16', 16'', 16s) to receive the force of air bag deployment from the dispenser (20, 20', 20'', 20s) and to direct and distribute that force against the door inner surface (38, 38', 38'', 38s) to separate the door (16, 16', 16'', 16s) from the vehicle panel (12, 12', 12'', 12s) along the frangible marginal edge (18, 18', 18'', 18s) of the door (16, 16', 16'', 16s).

2. A passive supplemental restraint apparatus (10, 10', 10'', 10s) as defined in claim 1 in which the door (16, 16', 16'', 16s) and vehicle panel (12, 12', 12'', 12s) are integrally formed as a single unitary piece by injection molding.

30

3. A passive supplemental restraint apparatus (10, 10', 10'', 10s) as defined in claim 1 in which the reaction plate (28, 28', 28'', 28s) includes a marginal outer edge portion (32, 32', 32'', 32s) having a shape generally identical to and aligned with at least a portion of the frangible marginal edge
5 (18, 18', 18'', 18s) of the air bag deployment door (16, 16', 16'', 16s).

4. A passive supplemental restraint apparatus (10, 10', 10'', 10s) as defined in claim 1 in which the reaction plate (28, 28', 28'', 28s) is attached to at least one of the air bag dispenser (20, 20', 20'', 20s) and the vehicle panel
10 (12, 12', 12'', 12s) along a reaction plate inner edge (34, 34', 34'', 34s) and in which an outer portion (35, 35', 35'', 35s) of the reaction plate (28, 28', 28'', 28s) is outwardly pivotable away from the air bag dispenser (20, 20', 20'', 20s) by bending the reaction plate (28, 28', 28'', 28s) along a first hinge line (36, 36', 36'', 36s) extending parallel to the attached reaction plate inner edge
15 (34, 34', 34'', 34s).

5. A passive supplemental restraint apparatus (10, 10', 10'', 10s) as defined in claim 1 in which at least a portion of the reaction plate (28, 28', 28'', 28s) is disposed adjacent the door inner surface (38, 38', 38'', 38s).
20

6. A passive supplemental restraint apparatus (10, 10', 10'', 10s) as defined in claim 5 in which at least one rib (40, 40s, 112, 114) extends integrally inward from the door inner surface (38, 38', 38'', 38s) toward the reaction plate (28, 28', 28'', 28s).
25

7. A passive supplemental restraint apparatus (10, 10', 10'', 10s) as defined in claim 1 in which the frangible marginal edge (18, 18', 18'', 18s) of the door (16, 16', 16'', 16s) comprises a region of reduced cross section.

8. A passive supplemental restraint apparatus (10, 10') as defined in claim 1 in which the air bag deployment door (16, 16') includes a rear
30

marginal edge that forms a hinge (44, 44') between the vehicle panel (12, 12') and the door (16, 16').

5 9. A passive supplemental restraint apparatus (10) as defined in claim 1 in which a flexible skin (69) covers at least a portion of the vehicle panel (12) in a layered disposition.

10 10. A passive supplemental restraint apparatus (10) as defined in claim 1 in which a foam layer (71) covers at least a portion of the vehicle panel (12).

15 11. A passive supplemental restraint apparatus (10, 10', 10'', 10s) as defined in claim 1 further including a first flexible tether (50, 50', 50'', 50s) connected to the door (16, 16', 16'', 16s) and fastened to at least one of the air bag dispenser (20, 20', 20'', 20s) and the vehicle panel (12, 12', 12'', 12s).

20 12. A passive supplemental restraint apparatus (10s) as defined in claim 11 in which the first flexible tether (50s) slidably engages the door (16s).

25 13. A passive supplemental restraint apparatus (10s) as defined in claim 12 in which a flexible strap (126) is fastened to the door (16s) at first and second spaced attachment points (128, 130), a portion of the first flexible tether (50s) slidably extending between the door (16s) and the strap (126) and between the first and second attachment points (128, 130).

30 14. A passive supplemental restraint apparatus (10s) as defined in claim 13 in which:

 first and second bosses (144, 146) extend integrally inward from a door inner surface (38s) to the respective first and second attachment points (128, 130); and

first and second fasteners (152) attach the strap (126) to the respective first and second bosses (144, 146).

15. A passive supplemental restraint apparatus (10s) as defined in
5 claim 13 in which the first flexible tether (50s) engages the reaction plate (28s).

16. A passive supplemental restraint apparatus (10s) as defined in claim 15 in which:

10 the reaction plate (28s) is attached to at least one of the air bag dispenser (20s) and the vehicle panel (12s) along a reaction plate inner edge (34s);

an outer portion (35s) of the reaction plate (28s) is outwardly pivotable away from the air bag dispenser (20s) by bending the reaction plate (28s) along a hinge line (36s) extending parallel to the reaction plate inner edge (34s);

the first flexible tether (50s) includes a tether loop (157) extending from at least one tether loop attachment portion (156, 158), the tether loop attachment portion (156, 158) fastened to at least one of the air bag dispenser (20s) the vehicle panel (12s) and the reaction plate (28s) adjacent the reaction plate hinge line (36s);

a middle tether portion (160) of the first flexible tether (50s) is disposed between the first and second tether loop ends (156, 158) and slidably engages the outer portion (35s) of the reaction plate (28s); and

25 an outer portion of the first flexible tether (50s) disposed between the middle tether portion (160) and the first tether loop end (156) slidably extends between the door (16, 16', 16'', 16s) and the strap (126).

17. A passive supplemental restraint apparatus (10s) as defined in
30 claim 16 in which an upper edge portion (44s) of the frangible marginal edge (18s) of the door (16s) extends generally parallel to and is spaced from the reaction plate hinge line (36s).

18. A passive supplemental restraint apparatus (10s) as defined in claim 16 in which the first flexible tether (50s) slidably extends through an opening (168) in the outer portion (35s) of the reaction plate (28s) adjacent a reaction plate outer marginal edge (32s).

[The tethers 50s, 51s pass through respective outer reaction plate slots, representatively shown at 168 in Figs. 12 and 13. The outer slots 168 are spaced parallel to and adjacent the reaction plate outer edge 32s. The tethers 50s, 51s also pass through respective inner reaction plate slots, representatively shown at 170 in Figs. 12 and 13. The inner slots 170 are spaced parallel to and adjacent the hinge line 36s.]

19. A passive supplemental restraint apparatus (10s) as defined in claim 12 in which at least one additional flexible tether (51s) slidably engages the door (16s).

20. A passive supplemental restraint apparatus (10, 10') as defined in claim 4 further including a first flexible tether (50, 50') having an outer end portion (52, 52') fastened to the door (16, 16') and an inner end portion (54, 54') fastened to the air bag dispenser (20, 20') at a point adjacent the reaction plate inner edge (34, 34').

21. A passive supplemental restraint apparatus (10, 10'', 10s) as defined in claim 11 in which the first tether (50, 50'', 50s) has an inner end portion (54, 82'', 82s) fastened to the air bag dispenser (20, 20'', 20s) at a point adjacent the reaction plate inner edge (34, 34'', 34s).

22. A passive supplemental restraint apparatus (10) as defined in claim 11 in which the first tether (50) has an outer end portion (52) fastened to the door inner surface (38) by at least one heat-staked pin (68), the pin (68) extending integrally inward from the air bag deployment door (16).

23. A passive supplemental restraint apparatus (10') as defined in claim 11 in which the tether (50') is fastened to the door inner surface (38') by a screw threaded into a boss, the boss extending integrally inward from the air bag deployment door (16').

24. A passive supplemental restraint apparatus (10', 10'') as defined in claim 11 in which the door (16', 16'') includes at least one fastener bracket extending integrally inward toward the air bag dispenser (20', 20'') from the door inner surface (38', 38''), the fastener bracket including an attachment surface spaced inwardly from the door inner surface (38', 38''), the first tether (50', 50'') attached to the attachment surface by a fastener.

25. A passive supplemental restraint apparatus (10', 10'') as defined in claim 24 in which the fastener bracket includes a fastener aperture disposed through the attachment surface of the bracket and in which the fastener comprises a rivet having a shaft portion extending through the aperture.

26. A passive supplemental restraint apparatus (10', 10'') as defined in claim 24 in which at least one of the fastener brackets extends integrally inward from the door inner surface (38', 38'') adjacent a lower marginal region of the door (16', 16'') to a point adjacent the reaction plate (28', 28'').

27. A passive supplemental restraint apparatus (10') as defined in claim 11 further including a second flexible tether (80) having an inner end portion fastened to at least one of the air bag dispenser (20') and the vehicle panel (12'), the outer end portion of the first tether (50') fastened to a forward portion of the door (16') adjacent a forward marginal edge of the door (16'), the second flexible tether (80) having an outer end portion fastened to an aft portion of the door (16').

28. A passive supplemental restraint apparatus (10') as defined in claim 27 in which a single sheet of flexible material comprises both the first and second tethers (50', 80).

5 29. A passive supplemental restraint apparatus (10, 10', 10'', 10s) as defined in claim 8 in which the air bag receptacle (26, 26', 26'', 26s) includes a mouth disposed adjacent the air bag deployment door (16, 16', 16'', 16s), the mouth having a width measured across the mouth in a direction perpendicular to the hinge, the hinge spaced from the mouth a distance equal
10 to at least half of the mouth width.

30. A passive supplemental restraint apparatus (10', 10'') as defined in claim 4 further including a stop member (96, 96'') operatively connected between the reaction plate (28', 28'') and at least one of the air bag dispenser
15 (20', 20'') and the vehicle panel (12', 12'').

31. A passive supplemental restraint apparatus (10', 10'') as defined in claim 30 in which:

the stop member (96, 96'') is connected to the reaction plate (28',
20 28'') at a stop point disposed between the first hinge line (36', 36'') and a reaction plate outer marginal edge (32', 32'') opposite the reaction plate inner edge (34', 34''); and

an outer portion (35', 35'') of the reaction plate (28', 28'') is outwardly pivotable away from the air bag dispenser (20', 20'') by bending
25 the reaction plate (28', 28'') along a second hinge line extending adjacent the stop point and generally parallel to the first hinge line (36', 36''), the second hinge line spaced between the first hinge line (36', 36'') and the reaction plate outer marginal edge (32', 32'').

30 32. A passive supplemental restraint apparatus (10', 10'') as defined in claim 30 in which:

the stop member (96, 96'') includes a pin having an elongated shaft portion (104, 104'') and a stop flange (108, 108'') disposed at an inner distal end of the shaft portion (104, 104''), the shaft portion (104, 104'') having a central longitudinal axis and a width measured across the shaft in a direction perpendicular to the axis, the stop flange (108, 108'') extending integrally and radially outward from the shaft portion (104, 104''); and in which

the air bag dispenser (20', 20'') includes an elongated slot (98, 98'') having a slot width slightly greater than that of the stop member shaft portion (104, 104''), the stop member shaft portion (104, 104'') slidably disposed within the slot (98, 98''), the stop member (96, 96'') movable between a stowed position and a deployed position under the force of an inflating air bag, the stop flange (108, 108'') being engaged with the slot (98, 98'') in the deployed position.

33. A passive supplemental restraint apparatus (10'', 10s) as defined in claim 1 in which the frangible marginal edge (18'', 18s) defines the entire air bag deployment door perimeter.

34. A passive supplemental restraint apparatus (10'', 10s) as defined in claim 33 in which at least one rib (112, 114, 112s, 40s) extends integrally inward from the door inner surface (38'', 38s) to a point adjacent the reaction plate (28'', 28s).

35. A passive supplemental restraint apparatus (10'', 10s) as defined in claim 33 in which a plurality of ribs (116, 116s) extend integrally inward from an inner surface of the vehicle panel (12'', 12s) adjacent the frangible marginal edge (18'', 18s) of the door perimeter and are spaced apart around the door perimeter.

36. A passive supplemental restraint apparatus (10'', 10s) as defined in claim 33 in which the frangible marginal edge (18'', 18s) of the door (16'', 16s) comprises a region of reduced cross section.

37. A passive supplemental restraint apparatus (10", 10s) as defined in claim 33 in which the reaction plate (28", 28s) includes a marginal edge portion (32", 32s) having a shape generally identical to and aligned with at least a portion of the frangible marginal edge (18", 18s) of the air bag deployment door (16", 16s).

38. A passive supplemental restraint apparatus (10", 10s) as defined in claim 33 in which the reaction plate (28", 28s) is rigidly attached to at least one of the air bag dispenser (20", 20s) and the vehicle panel (12", 12s) along a reaction plate inner edge (34", 34s) and in which an outer portion (35", 35s) of the reaction plate (28", 28s) is outwardly pivotable away from the air bag dispenser (20", 20s) by bending the reaction plate (28", 28s) along a first hinge line (36", 36s) extending parallel to the rigidly attached reaction plate inner edge (34").

39. A passive supplemental restraint apparatus (10", 10s) as defined in claim 33 further including a flexible tether (50", 50s) fastened between the door (16", 16s) and the reaction plate (28", 28s).

40. A passive supplemental restraint apparatus (10") as defined in claim 39 in which the tether (50") includes an inner end portion (82") fastened to the door (16"), an outer end portion (84") fastened to the door (16") and a middle portion (83) fastened to the reaction plate (28", 28s), the middle portion (83) of the tether (50") disposed between the inner and outer end portions (82", 84") of the tether (50").

41. A passive supplemental restraint apparatus (10") as defined in claim 39 in which the door (16") includes a fastener bracket (70") extending integrally inward toward the air bag dispenser (20") from the door inner surface (38"), the fastener bracket (70") including an attachment surface

spaced inwardly from the door inner surface (38"), the tether (50") attached to the attachment surface by a fastener (76").

42. A passive supplemental restraint apparatus (10") as defined in
5 claim 41 in which the fastener bracket (70") includes a fastener aperture disposed through the attachment surface of the bracket (70") and in which the fastener (76") comprises a rivet having a shaft portion extending through the aperture.

10 43. A passive supplemental restraint apparatus (10") as defined in claim 39 in which the tether (50") is fastened to the door inner surface (38") by at least one heat-staked pin (76"), the pin (76") extending integrally inward from the air bag deployment door (16").

15 44. A passive supplemental restraint apparatus (10") as defined in claim 39 in which the tether (50") is fastened to the door inner surface (38") by a screw (76b) threaded into a boss (67), the boss (67) extending integrally inward from the air bag deployment door (16").

20 45. A passive supplemental restraint apparatus (10") as defined in claim 38 further including a flexible tether (50") fastened between the door (16") and the reaction plate (28") and a stop member (96") operatively connected between the reaction plate (28") and the air bag dispenser (20").

25 46. A passive supplemental restraint apparatus (10") as defined in claim 45 in which:

the stop member (96") is connected to the reaction plate (28") at a stop point disposed between the first hinge line (36") and a reaction plate outer marginal edge (32") opposite the reaction plate inner edge (34");

30 the outer portion (35") of the reaction plate (28") is outwardly pivotable away from the air bag dispenser (20") by bending the reaction plate (28") along a second hinge line (102") extending adjacent the stop point and

generally parallel to the first hinge line (36"), the second hinge line (102") spaced between the first hinge line (36") and the reaction plate outer marginal edge (32"); and

the tether (50") is attached to the reaction plate (28") between the
5 second hinge line (102") and the reaction plate outer marginal edge (32").

47. A passive supplemental restraint apparatus (10") as defined in claim 46 in which:

the stop member (96") includes a pin having an elongated shaft
10 portion (104") and a stop flange (106") disposed at an inner distal end of the shaft portion (104"), the shaft portion (104") having a central longitudinal axis and a width measured across the shaft in a direction perpendicular to the axis, the stop flange (106") extending integrally and radially outward from the shaft portion (104"); and in which

the air bag dispenser (20") includes an elongated slot (98") having
15 a slot width slightly greater than that of the stop member shaft portion (104"), the stop member shaft portion (104") slidably disposed within the slot (98"), the stop member (96") movable between a stowed position and a deployed position under the force of an inflating air bag, the stop flange (106") being
20 engaged with the slot (98") in the deployed position.




FIG-1










FIG-2













FIG - ~~10~~ 11



INTERNATIONAL SEARCH REPORT

International application No.

PCT/US98/07774

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :B60R 21/20, 21/22

US CL :280/728.3, 732

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 280/728.3, 732, 728.1, 728.2, 730.1, 730.2, 752

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	JP 5-185896 A (AOYAMA et al.) 27 July 1993 (27/07/93), Figs. 3-8.	1-5, 7-11, 20, 30
Y	US 4,911,471 A (HIRABAYASHI) 27 March 1990 (27/03/90) see entire document	1-5, 7-10, 20
Y	US 5,385,366 A (FRANK et al.) 31 January 1995 (31/01/95) see entire document	1-5, 7-11, 20, 21, 30, 33, 35-38
Y	US 5,072,967 A (BATCHELDER et al.) 17 December 1991 (17/12/91) see entire document	1-5, 7, 9-11, 20, 21, 30, 33, 35-38

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document published on or after the international filing date	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

15 JUNE 1998

Date of mailing of the international search report

16 JUL 1998

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

for PETER ENGLISH

Telephone No. (703) 308-1113

INTERNATIONAL SEARCH REPORT

international application No.

PCT/US98/07774

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,330,223 A (HIRAMITSU et al.) 19 July 1994 (19/07/94) see entire document	35

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US98/07774

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This international report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☒ Claims Nos.: 12-19
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

the description is not clear and complete, as required by Article 5, since Figs. 12-16 are not included in the drawings.
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
☐ No protest accompanied the payment of additional search fees.